



TREND TIMBERS

One Stop Woodworking

Phone: +61 2 4577 5277
Email: sales@trendtimbers.com.au
Visit: 15 Railway Rd North
Mulgrave NSW 2756



19-38 Drum Sander



PRODUCT FEATURES

Simple adjustment feature- one adjustment nut to align the conveyor to the sanding head – makes the process fast and easy

Easy height adjustment – a thrust bearing below the handle and a nut above prevents the drum moving out of set position while sanding

Extra wide conveyor to properly support stock over 480mm wide

Drum carriage bolted to the base preventing any alignment issues

INTELLSAND Technology – adjusts conveyor speed based on load prevents gouging and burning – provides a consistent finish

Digital depth gauge

TECHNICAL INFORMATION

Max. Thickness: 100mm
Min. Thickness: 0.8mm

Min. Length: sanding – 60mm
Max. Width of cut – 960mm (2passes)

Drum speed: 1740RPM

Conveyor Speed: Variable 0-3m/min
Conveyor Motor: Direct Drive, DC

Main Motor: 1 1/2 HP single phase
Dust port: 1 x 100mm

Dimensions: 1460 x 860 x 1450mm
Net weight: 155kg

OPTIONAL Stand and infeed/outfeed tables available

www.trendtimbers.com.au